

Описание на фотометры. Серия VisGuard

По вопросам продаж и поддержки обращайтесь: ssg@nt-rt.ru www.sigrisnt-rt.ru

Архангельск (8182)63-90-72,
Астана+7(7172)727-132,
Белгород(4722)40-23-64,
Брянск(4832)59-03-52,
Владивосток(423)249-28-31,
Волгоград(844)278-03-48,
Вологда(8172)26-41-59,
Воронеж(473)204-51-73,
Екатеринбург(343)384-55-89,
Иваново(4932)77-34-06,
Ижевск(3412)26-03-58,
Казань(843)206-01-48,
Калининград(4012)72-03-81,
Калуга(4842)92-23-67,
Кемерово(3842)65-04-62,
Киров(8332)68-02-04,

Краснодар(861)203-40-90,
Красноярск(391)204-63-61,
Курск(4712)77-13-04,
Липецк(4742)52-20-81,
Магнитогорск(3519)55-03-13,
Москва(495)268-04-70,
Мурманск(8152)59-64-93,
НабережныеЧелны(8552)20-53-41,
НижнийНовгород(831)429-08-12,
Новокузнецк(3843)20-46-81,
Новосибирск(383)227-86-73,
Орел(4862)44-53-42,
Оренбург(3532)37-68-04,
Пенза(8412)22-31-16,
Пермь(342)205-81-47,
Ростов-на-Дону(863)308-18-15,

Рязань(4912)46-61-64,
Самара(846)206-03-16,
Санкт-Петербург(812)309-46-40,
Саратов(845)249-38-78,
Смоленск(4812)29-41-54,
Сочи(862)225-72-31,
Ставрополь(8652)20-65-13,
Тверь(4822)63-31-35,
Томск(3822)98-41-53,
Тула(4872)74-02-29,
Тюмень(3452)66-21-18,
Ульяновск(8422)24-23-59,
Уфа(347)229-48-12,
Челябинск(351)202-03-61,
Череповец(8202)49-02-64,
Ярославль(4852)69-52-93



Applications

- Visibility measurement
- Ventilation control
- Early fire warning in road and railway tunnels


Features

- Sampling either in-situ or extractive
- Installation in tunnel, in niches or in control room
- Operation locally or centrally with multichannel control
- Highly stable readings thanks to purge air
- Annual check with standard
- Easy zero-point check even in dusty conditions
- Mist problems eliminated by heating

VISIBILITY MONITOR VISGUARD

FUNDAMENTALS

Visibility measurement



Visibility, CO concentration, and sometimes also NO concentration are the measurable criteria for assessing air quality in road tunnels. These parameters are therefore used for controlling the ventilation system in order to minimize energy consumption and also for closing down the tunnel whenever preestablished limits are exceeded.

Visibility is stated in the form of an extinction coefficient that corresponds to the light attenuation caused by air pollution. It is possible to use either the level of transmitted light or scattered light as basis of the measuring system, because most of the light attenuation is caused by scatter effects. The scattered light intensity is multiplied by a factor to obtain the extinction coefficient.

Measuring method

The VisGuard measures the scattered light intensity of a sample drawn into the instrument from the tunnel. This configuration permits extremely simple installation without time-consuming adjustment, reliable checking and correction of the zero and reference points without ambient air effects, and the ability to carry out measurement either inside or outside the tunnel cavity. An optional heater at the sample inlet effectively eliminates any troublesome mist effects.

The VisGuard employs a variation of the long-proven SIGRIST dual-beam measuring method. It determines the relation between the light scattered at a 30° angle and the directly transmitted light. This system elegantly eliminates the effects of any light source fluctuations as well as ageing or temperature effects of the electronics.

Early fire warning


To achieve the earliest possible detection of hot or cold fires producing smoke, a second current output or a limit contact with a much higher threshold value can be set entirely independent of measuring range used for visibility. By detecting fires early, this system opens up new possibilities for improving tunnel safety.

Sample extraction

The tunnel air is extracted by a blower and carried through the flow cell. In the in-situ version the blower is integrated in the sensor. For the extractive arrangement, separate fans are used because more power is required.


The blower also feeds filtered purge air to the flow cell, thus enveloping the sample in a protective shroud of clean purge air. This effectively keeps the optics clean and minimizes drift caused by fouling.

INSTALLATION ALTERNATIVES



In-situ


The least costly place to install the VisGuard is right in the tunnel cavity or in an emergency niche. The VisGuard is simply fastened to the wall or ceiling. The integrated blower draws in the ambient air and passes it through the flow cell for measurement. Access to the instrument is required only for the annual adjustment and filter change.



Extractive single sampling

If the operator wants to keep the tunnel as free as possible from technical equipment, or if very easy access to the instrument is desired, the extractive arrangement can be used. In this case a separate fan draws the sample from the extraction point in the tunnel and transports it to the sensor through a sample pipe.

Thanks to its compact design, the VisGuard can be installed close to the tunnel cavity or under it in emergency cabins, transverse tunnels or the equipment gallery with just a few meters of extraction distance, or else in a control room as far as 500 m away.



Extractive multiple sampling

Extractive sampling also opens up the possibility of carrying extraction pipes from up to 4 sampling points via a valve unit to a single sensor. With the multichannel control unit SIBUS, the continuous sample flows from the different extraction points are fed cyclically to the VisGuard. In this case the maximum extraction length is 200 m. This configuration has proven highly effective for more intensive monitoring of certain tunnel sections.

Installation/Mounting

In-situ mounting is a matter of fastening the VisGuard to the wall with 2 screws. If the sample is withdrawn extractively, the instrument can be installed on a wall or in a suitable cabinet. For installations employing multiple sampling, installation in a cabinet is recommended.

OPERATION AND COMMUNICATION

With its two-line LC display and operating structure with plain-text guidance, SIREL provides extremely easy access to the VisGuard for operation, configuration and servicing. It has two 0/4.. 20 mA current outputs and two independent relay contacts that can serve as either limit or alarm contacts.

SIREL can be installed remotely up to 100 m away from the VisGuard. The SIREL robust version, with covered display and keypad, is available for installation right in the tunnel.

An optional BUS coupler is available for connection to PROFIBUS DP. It allows direct data transmission and ventilation control via the digital interface.

The terminal box SIPOINT PB provides a direct connection of the VisGuard to Profibus DP. Operation of the VisGuard is done via the Profibus DP serial interface or via the SIPOINT C that can be connected to the SIPOINT PB.

As many as 8 detection points can be queried and configured centrally from the control room with SIBUS. The advantage over individual control units at the instruments is that, in addition to the readings, status signals are also available at all times so that instrument parameters can be altered as required.

In this case a SITRA transmitter located right at the VisGuard provides the connection to an RS 485 bus, takes care of the power supply, and conditions the bus signal.

Additional sensors, e.g. for measuring CO, NO or wind velocity, can be connected to analog inputs on SIBUS, so that all of the important information for controlling tunnel ventilation is available right at one spot. Furthermore, it is possible to connect an analog signal to the VisGuard and to transmit it with the others via the bus to SIBUS.

Detailed information on SIBUS capabilities is given in a separate Data Sheet.

Calibration of the SIGRIST VisGuard is carried out at the factory using PLA (polystyrene-latex aerosol) as the defined medium. For visibility measurement, the PLA value is converted to the extinction coefficient.

For the annual calibration check, a checking rod is available that permits correction of the instrument in a matter of seconds. If necessary, the zero point can be checked at the same time by interrupting the air supply.

**Single control unit
SIREL**


Connection box SIPOINT PB

**Multichannel control unit
SIBUS**


Calibration

DIMENSIONS AND CONNECTIONS


Dimensions




VisGuard Extractive



Control Unit SIREL SMD




SIPORT PB




VisGuard In-situ with sample heater

Connecting diagram SIREL SMD



Connecting diagram SIPORT PB (variation)



SPECIFICATIONS

Visibility measurement

Measuring principle:	30° scattered light measurement
Measuring span:	0 .. 100 PLA
Measuring ranges:	0 .. $15 \cdot 10^{-3}$ E/m; 7 additional freely configurable ranges
Resolution:	< ± 0.25 % of full scale value
Measuring wavelength:	880 nm

Photometer VisGuard

Enclosure material:	stainless steel 1.4571
Sample temperature:	-20 °C .. +50 °C
Flowrate:	5 l/min (In-situ) / 25 .. 30 l/min (extractive)
Ambient temperature:	-20 °C .. +50 °C
Ambient pressure:	±3000 Pa (±30 mbar)
Protection type:	IP65
Weight:	6.5 kg (In-situ) / 5.0 kg (extractive)
Depth from wall:	235 mm
Sample heater (optional):	230 VAC; 25 W

Control Unit SIREL SMD

Power supply:	85 .. 264 VAC / 47 .. 440 Hz
Power consumption:	25 W
Current output:	0/4 .. 20 mA; burden max. 600 Ω
Contacts:	2 separately configurable relay contacts 250 VAC, 4 A
Protection type:	IP65
Weight:	1.5 kg
Connection to VisGuard:	4-core cable, up to 100 m

Connection box SIPOPT PB

Power supply:	85 .. 264 VAC / 47 .. 63 Hz
Power consumption:	10 W / 25 W (with heater)
Bus (version PB):	Profibus DP
Degree of protection:	IP65
Material:	Polyester, glass-fiber reinforced
Weight:	0.85 kg
Connection to VisGuard:	4-core cable, up to 100 m

Sampling system 0 .. 30 m

Blower type:	SE12
Power supply:	230 VAC / 50 Hz
Power consumption:	90 W
Ambient temperature:	-20 °C .. +40 °C
Degree of protection:	IP54
Weight:	7 kg
Sample heater (optional):	230 VAC; 42 W (extractive)

Sampling system 30 .. 500 m and multiple sampling

Blower type:	SE4n	SD4n
Power supply:	230 VAC / 50 or 60 Hz	3x 400 VAC / 50 or 60 Hz 3x 440 VAC / 50 or 60 Hz
Power consumption:	1 - 1.5 kW	950 W - 1.6 kW
Ambient temperature:	-20 °C .. +40 °C	
Degree of protection:	IP54	
Weight:	22 kg	
Sample heater (optional):	230 VAC; 42 W (extractive)	

По вопросам продаж и поддержки обращайтесь: ssg@nt-rt.ru www.sigrisnt-rt.ru

Архангельск (8182)63-90-72,
Астана+7(7172)727-132,
Белгород(4722)40-23-64,
Брянск(4832)59-03-52,
Владивосток(423)249-28-31,
Волгоград(844)278-03-48,
Вологда(8172)26-41-59,
Воронеж(473)204-51-73,
Екатеринбург(343)384-55-89,
Иваново(4932)77-34-06,
Ижевск(3412)26-03-58,
Казань(843)206-01-48,
Калининград(4012)72-03-81,
Калуга(4842)92-23-67,
Кемерово(3842)65-04-62,
Киров(8332)68-02-04,

Краснодар(861)203-40-90,
Красноярск(391)204-63-61,
Курск(4712)77-13-04,
Липецк(4742)52-20-81,
Магнитогорск(3519)55-03-13,
Москва(495)268-04-70,
Мурманск(8152)59-64-93,
НабережныеЧелны(8552)20-53-41,
НижнийНовгород(831)429-08-12,
Новокузнецк(3843)20-46-81,
Новосибирск(383)227-86-73,
Орел(4862)44-53-42,
Оренбург(3532)37-68-04,
Пенза(8412)22-31-16,
Пермь(342)205-81-47,
Ростов-на-Дону(863)308-18-15,

Рязань(4912)46-61-64,
Самара(846)206-03-16,
Санкт-Петербург(812)309-46-40,
Саратов(845)249-38-78,
Смоленск(4812)29-41-54,
Сочи(862)225-72-31,
Ставрополь(8652)20-65-13,
Тверь(4822)63-31-35,
Томск(3822)98-41-53,
Тула(4872)74-02-29,
Тюмень(3452)66-21-18,
Ульяновск(8422)24-23-59,
Уфа(347)229-48-12,
Челябинск(351)202-03-61,
Череповец(8202)49-02-64,
Ярославль(4852)69-52-93